

# Vacuum pump (oil-free)

**ROCKER**  
make filtration easy

## Rocker 430 -630 mmHg, 80 psi, up to 34 l/min



Rocker 430

### Ideal for:

- filtration for microbiology test
- air sampling
- suspended solid test
- vacuum filtration

### Features:

- lubricant and oil free piston
- no air pollution
- maintenance-free
- Prote™ filter prevents from liquid being sucked into the pump and filters particles as well as moisture
- CE certified

### Safety mechanism:

- thermal protection device ensures shutting down the pump when overheated and resumes working when the temperature cooled down

Model	Rocker 430	
Max. power (W)	147	125
Max. current (A)	1.5	0.6
Max. vacuum	-630 mmHg (173 mbar)	
Max. pressure	80 psi	
Max. flow rate	34 l/min	28 l/min
Moisture trap / vacuum regulator	Yes	
Overflow protection	Yes	
Motor ration	1700 rpm	1450 rpm
Horse power	1/6 HP	
Noise level	52 dB	
Port thread	5/16 inch (8 mm)	
Net weight	5.5 kg	
Dimension (LxWxH)	24.7 x 23 x 26.9 cm	
Power supply	1 Phase AC 120V, 60 Hz or AC 230V, 50/60 Hz	
Order number 110V	00829 167430-11	-
Order number 230V	-	00829 167430-22