



designed for scientists



## KS 260 basic

/// Data Sheet

Compact, flat orbital shaker with ideal swivel motion, for a maximum shaking weight of 7.5 kg.

- Electronic adjustment of speed and timer
- LED display for speed and time adjustment
- Wide range of attachment combinations makes it possible to use almost all shapes and sizes of vessels
- Attachments are not included, please order separately



designed for scientists

## Technical Data

|  |                                |
|--|--------------------------------|
| Type of movement                                   | orbital                        |
| Shaking stroke [mm]                                | 10                             |
| Permissible shaking weight (incl. attachment) [kg] | 7.5                            |
| Motor rating input [W]                             | 45                             |
| Motor rating output [W]                            | 10                             |
| Permissible ON time [%]                            | 100                            |
| Speed min (adjustable) [rpm]                       | 50                             |
| Speed range [rpm]                                  | 0 - 500                        |
| Speed display                                      | LED line                       |
| Timer  | yes                            |
| Timer display                                      | LED line                       |
| Time setting range [min]                           | 5 - 50                         |
| Operating mode                                     | timer and continuous operation |
| Dimensions (W x H x D) [mm]                        | 360 x 98 x 420                 |
| Weight [kg]  | 8.5                            |
| Permissible ambient temperature [°C]               | 5 - 50                         |
| Permissible relative humidity [%]                  | 80                             |
| Protection class according to DIN EN 60529         | IP 21                          |
| Analog output                                      | yes                            |
| Voltage [V]  | 220 - 240                      |
| Frequency [Hz]                                     | 50/60                          |
| Power input [W]                                    | 45                             |

