

KERN FEJ 62K-4DM

KERN

High-capacity precision balance with password-protected user administration



USP Minimum weight of sample (k = 2, U = 0.1%)	200 g
Minimum weight [Min] (ct)	25 ct
Adjustment options	Internal calibration (automatic)
Stabilization time	3 s
Warm-up time	120 min; 120 min
Eccentric loading at 1/3 [Max]	0,3 g; 3 g

Approval	
CE mark	✓
Accuracy classe	II
Verification scale interval [e]	1 g
Verification scale interval [e] (ct)	5 ct
Conformity assessment possible ex works	✓

Display	
Display type	LCD
Display type	LCD
Display screen size	172×58 mm
Display backlight	✓
Display digit height - smallest digit	8,5 mm
Display digit height	16,5 mm
Languages of the user interface	English

Construction	
Dimension display device (W×D×H)	290×180×80 mm
Dimension housing (W×D×H)	350×520×170 mm
Dimensions weighing platform (W×D×H)	400×350×150 mm
Material display housing	stainless steel
Material housing	stainless steel, cast iron
Material weighing plate	stainless steel
Material platform	Stainless steel
Dimensions weighing surface (W×D)	350×400 mm
Display device cable length	1 m
Levelling feet adjustable	✓
Wall mount	✓

Functions	
Number of keys for operation	9
Capacity - Display	✓
PreTare function	✓
Tare function	manual (multi)
Percentage determination	✓
Counting function	✓

Category	
Brand	KERN
Product category	Laboratory balance
Product group	Precision balance
Product family	FEJ

Measuring System	
Construction type of the scale	Multi-division balance
Weighing system	Tuning fork
Weighing capacity [Max]	6200 g; 62000 g
Weighing capacity [Max] (ct)	31000 ct; 310000 ct
Readability [d]	0,1 g; 1 g
Readability carat [d] (ct)	0,5 ct; 5 ct
Resolution	62.000, 62.000
Linearity	± 0,3 g; 3 g
Reproducibility	0,1 g; 1 g
Tare range	62000 g
Default unit	g kg g dwt tl (Tw) tl (HK) ozt tl (Singap, Malays) ct lb oz tol mom
Units (if device is conformity assessed)	kg g ct
Minimum weight [Min]	5 g

KERN FEJ 62K-4DM

High-capacity precision balance with password-protected user administration

Tolerance weighing	✓
Tolerance weighing - type of signal	acoustically visual
Standby function	✓
Recipe/summing level	Rez A (Net total)
Sum memory function	✓
Underfloor weighing	Hook (optional)
Interfaces	Digital I/O (optional, factory) RS-232 standard - 2x
IP protection - complete device	IP65
IP protection - display	IP65
IP protection - load cell	IP65
IP protection - platform	IP65

Counting

Smallest piece weight when piece counting - laboratory conditions	100 mg
Smallest piece weight when piece counting - normal conditions	1 g
Reference quantity	5, 10, 30, 50, 100, n (any number of pieces)
Counting resolution (laboratory conditions)	620.000

Power Supply

Input voltage power supply / power [Max]	100 V - 240 V AC, 50 / 60 Hz
Input voltage device / power [Max]	12 V, 1.0 A
Plug-in power supply type	Power adapter
Supplied power supply	Power supply unit
Plug-in power supply / adapter for countries - included with the delivery	EURO AUS UK US
Plug-in power supply / adapter for countries - optional	EURO AUS UK US CH
Rechargeable battery optional	Rchrg. battery optional (factory)
Rechargeable battery charging time	12 h
Rechargeable battery operating time - backlight off	10 h

Environmental conditions

Humidity of environment [Max]	80 %
Ambient temperature [Min]	5 °C

Ambient temperature [Max]	35 °C
---------------------------	-------

Packing & Shipping

Readability force [d] (N)	1 d
Dimensions packaging (W×D×H)	490×830×430 mm
Net weight	19 kg
Shipping method	Parcel service
Net weight approx.	19 kg
Gross weight approx.	26 kg
Shipping weight	35 kg

Services (optional)

Article number for DAkkS calibration	963-129
Article number for certificate of conformity (verification)	969-517

Pictograms

STANDARD



OPTION



FACTORY

