KERN **EHA 3000-0**



The compact all-round model with robust stainless steel weighing plate for use in laboratories, industries, and for teaching



Category	
Brand	KERN
Product categoriy	Laboratory balance
Product group	School balance
Product family	EHA

Measuring System	
Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	3000 g
Readability [d]	1 g
Resolution	3.000
Linearity	± 2 g
Reproducibility	3 g
Tare range	3000 g
Default unit	g
Units	g gn dwt ct oz
Adjustment options	Adjusting with external weight
Recommended adjusting weight	1 kg (M1); 3 kg (M1)
Possible calibration points	1 kg; 3 kg
Stabilization time	3 s
Warm-up time	10 min
Eccentric loading at 1/3 [Max]	3 g
Maximum creep (15 minutes)	4 g
Maximum creep (30 minutes)	8 g
Approval	

CE mark

Display	
Display type	LCD
Display screen size	75×32 mm
Display backlight	✓
Display digit height	22 mm
Languages of the user interface	Symbol language

Construction	
Dimension housing (W×D×H)	225×160×50 mm
Dimensions weighing platform (W×D×H)	120×120×7 mm
Material housing	ABS plastic
Material weighing plate	stainless steel
Dimensions weighing surface (W×D)	120×120 mm
Levelling feet adjustable	/

Functions	
Number of keys for operation	5
Auto-off interval(s) in battery mode/rechargeable battery mode	5 min
Tare function	manual (multi)
Counting function	✓

Counting	
Smallest piece weight when piece counting - laboratory conditions	1 g
Smallest piece weight when piece counting - normal conditions	10 g
Counting resolution (laboratory conditions)	3.000

Power Supply	
Input voltage power supply / power [Max]	100 V - 240 V, 50 / 60 Hz
Input voltage device / power [Max]	9 V, 600 mA
Plug-in power supply type	Power adapter
Supplied power supply	Power supply & battery function (battery not included)
Plug-in power supply / adapter for countries - included with the delivery	EURO UK CH
Plug-in power supply / adapter for countries - optional	EURO UK CH
Battery	2×1.5 V AA
Battery / accumulator type	Alkali(-Manganese)

1

KERN **EHA 3000-0**



The compact all-round model with robust stainless steel weighing plate for use in laboratories, industries, and for teaching

Battery connection	Battery insert
Battery operating time	70 h

Environmental conditions	
Humity of environment [Max]	80 %
Ambient temperature [Min]	5 °C
Ambient temperature [Max]	40 °C
Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C

Packing & Shipping	
Readability force [d] (N)	1 d
Dimensions packaging (W×D×H)	245×204×76 mm
Net weight	0,5 kg
Shipping method	Parcel service
Net weight approx.	0,50 kg
Gross weight approx.	0,75 kg
Shipping weight	0,8 kg

Services (optional)	
Article number for adjustment at the location of installation	961-247
Article number for DAkkS calibration	963-127
Article number for certificate of conformity (verification)	969-517

Pictograms

STANDARD















OPTION

