

IKA

designed for scientists



RV 8 with Dry Ice Condenser, coated

/// Data Sheet

The IKA Rotary Evaporator range gets a new family member - the RV 8. This new distilling system completes the existing series by adding a functional basic model. The manual lift, with ambidextrous design, allows for precise positioning of the glassware. Digital displays for rotation speed and heating bath temperature allow for optimal control of all distilling processes. New clamp mechanism to simplify the changing of evaporation flasks.

- Manual lift with integrated safety "lift-out-function"
- New clamp mechanism
- Water/oil heating bath with integrated ergonomic carrying handles
- Key-button with locking function for the heating bath temperature

www.ika.com

Subject to technical changes





designed for scientists

- Speed range 5 - 300 rpm
- Single-hand operation; ambidextrous design
- Adjustable immersion angle
- Additional user safety through reduced 24 V power requirements within the unit
- Compatible with the complete range of IKA RV 10 glassware

Package description: With heating bath HB digital and RV 10.40 Dry Ice Condenser coated



designed for scientists

Technical Data

Type of cooling	Dry ice condenser
Cooling surface [cm ²]	620
Motor principle	DC
Speed range [rpm]	5 - 300
Speed tolerance set rotation speed lt; 100rpm [rpm]	±1
Speed tolerance set rotation speed gt; 100rpm [%]	±1
Lift	manual
Stroke [mm]	120
Heating temperature range [°C]	room temp. - 180
Heat output [W]	1400
Set temperature resolution [K]	±1
Filling volume max. [l]	4
Dimensions (W x H x D) [mm]	510 x 490 x 345
Weight [kg]	25.76
Permissible ambient temperature [°C]	5 - 40
Permissible relative humidity [%]	80
Protection class according to DIN EN 60529	IP 20
Voltage [V]	100 - 240
Frequency [Hz]	50/60
Power input [W]	1500
DC Voltage [V=]	24